



Firstly, establish how you will want the blinds to be mounted; face fix or reveal fix. Check that you have a good fixing point for the head box (you can screw through the ends, the back or the top of a fully enclosed headbox).

### REVEAL FIX

- 1 Accurately measure the top of the opening. Look for the narrowest point where the hood will be slid in and where it will be mounted. We will make the hood 2mm narrower than your advised top opening.
- 2 Measure the centre and bottom openings and record.
- 3 Check both sides to see if they are level horizontally. Make a note on your order if a side is out by more than 10mm.
- 4 Measure the drop from the top of the opening to the ground.

### FACE FIX

- 1 Measure the points at which the headbox will be fitted, outside of headbox to outside of headbox, and record as the top measurement.
- 2 Normally the centre and bottom measurements are the same.
- 3 Measure the drop from the top of the required hood position to the ground.
  - For a single opening, we recommend adding 55mm to each side of the opening measurements (110mm overall) for final width measurements. This will keep the fixings for mounting the face fix angles away from the corners for strong fixing points and so that the tracks will not be visible from the inside of the opening.
  - For multiple adjacent openings, pairs of blinds can be measured to meet against a single face fix angle, effectively butting up together with channels fixed back to back on either side of the angle.
- 4 A Face Fit Channel is also available to save having to fit the angle first.